

FSW17K

Flange Spreading Wedge

A Hydraulic Flange Spreading Wedge actuated by 700bar hydraulics.

The FSW17 flange spreading wedge can enter a flange joint access gap as small as 6mm and produce a maximum force of 326kN when used in pairs (as recommended) to push the mating faces of flanges apart.

The FSW17 can create a gap up to 81mm between flange faces with the stepped blocks fitted facilitating the replacement of gaskets, seal ring's, or other flange face maintenance and testing.

- 100% Load/Pressure tested and certified
- High durability High Quality low Maintenance design
- Tool weight 7Kg
- Max Spreading force 163kN (326kN when used in pairs)
- Spreading distance 6mm to 81mm (when used with stepped blocks)
- Robust Moulded Case for easy transportation and storage




Engineered Energy Equipment

Product Sales | Product Rental | Bespoke Solutions

FSW17K

Flange Spreading Wedge



Kit weight: 12Kg

Kit Dims.: 580mm x 340mm x 180mm

Tool Weight: 7Kg

Tool Dims.: 76mm x 155mm x 350mm

Product ordering code: FSW17K

Kit Content

- 1 x FSW17 Tool
- 1 x Safety Block
- 1 x Safety Lanyard
- 2x Stepped Blocks with securing screws and allen key
- 1 x Instruction Manual
- 1 x Robust moulded carry case



Engineered Energy Equipment

Product Sales | Product Rental | Bespoke Solutions

www.renquip.com

Unit 1 Dunnottar House, Howe Moss Drive, Dyce, Aberdeen, AB21 0FN
+44(0) 1224001861 | info@renquip.com